WARNING

IMPORTANT NOTICE DO NOT DETACH

SUPERFUND CONFIDENTIAL BUSINESS INFORMATION

All or a portion of the attached document is claimed to be confidential business information by the submitter pursuant to CERCLA, as amended, § 104. Unless and until EPA makes a determination that the document is not confidential business information, it must be treated as such.

Any person handling or using the attached document in any way is responsible for preventing unauthorized disclosure while in his or her possession. §1905 of title 18 of the United States Code and CERCLA, as amended, §104(e)(7)(B) provide penalties for disclosure of confidential business information. They include criminal penalties and adverse personnel actions.

The document may not be disclosed further or copied by you except as authorized by The Superfund CBI Manual. If you have any questions concerning the appropriate handling of this document, please contact the attorney assigned to this case or the Office of Regional Counsel, EPA, Region 9.

CONFIDENTIAL

GIBSON, DUNN & CRUTCHER

LAWYERS 333 SOUTH GRAND AVENUE

LOS ANGELES, CALIFORNIA 90071-3197

(213) 229-7000 TELEX: 674930 GIBTRASK LSA FACSIMILE: (213) 229-7520

June 24, 1992 2

SFUND RECORDS CTR 2166-03164

JAS. A. GIBSON, IBS2-1922 W. E. DUNN, IB61-1925 ALBERT CRUTCHER, IB60-1931

NEW YORK

200 PARK AVENUE NEW YORK, NEW YORK 10166-0193

WASHINGTON

1050 CONNECTICUT AVENUE N.W. WASHINGTON, D.C. 20036-5306

BRUSSELS

AVENUE LOUISE 222 B-1050 BRUSSELS, BELGIUM

PARIS 104 AVENUE RAYMOND POINCARÉ 75116 PARIS, FRANCE

LONDON

30/35 PALL MALL LONDON SWIY SLP

HONG KONG 8 CONNAUGHT PLACE HONG KONG

TOKYO

- 1-1-3 MARUNOUCHI, CHIYODA-KU

AFFILIATED SAUDI ARABIA OFFICE CHAMBER OF COMMERCE BUILDING P.O. BOX 15870 RIYADH 11454, SAUDI ARABIA

OUR FILE NUMBER

G 37336-00001

CENTURY CITY 2029 CENTURY PARK EAST LOS ANGELES, CALIFORNIA 90067-3026

ORANGE COUNTY 800 NEWPORT CENTER DRIVE NEWPORT BEACH, CALIFORNIA 92660-6395

SACRAMENTO 400 CAPITOL MALL SACRAMENTO, CALIFORNIA 95814

SAN DIEGO 750 B STREET

SAN DIEGO, CALIFORNIA 92101-4605 SAN FRANCISCO

ONE MONTGOMERY STREET, TELESIS TOWER SAN FRANCISCO, CALIFORNIA 94104-4505

SAN JOSE 50 WEST SAN FERNANDO STREET SAN JOSE, CALIFORNIA 95113

DALLAS 1717 MAIN STREET DALLAS, TEXAS 75201-4605

DENVER 1801 CALIFORNIA STREET DENVER, COLORADO 80202-2694

SEATTLE 999 THIRD AVENUE SEATTLE, WASHINGTON 98104-7089

WRITER'S DIRECT DIAL NUMBER 229-7814

VIA FEDERAL EXPRESS

Chris Stubbs South Coast Groundwater Section, H-6-4 United States Environmental Protection Agency Post Office Box 193062 San Francisco, CA 94119-3036

> Hawker Pacific Inc. 11310 Sherman Way

Sun Valley, California; EPA Reference T-4-1

Dear Mr. Stubbs:

Enclosed is the response of Hawker Pacific Inc. to EPA's third request for information to it pertaining to the above facility.

If you have any questions regarding this response, please call me.

Very truky yours,

Míchael A. Monahan

MAM/par

LL921760.171

MICHAEL A. MONAHAN
GIBSON, DUNN & CRUTCHER
333 South Grand Avenue
Los Angeles, California 90071
(213) 229-7000

Attorneys for HAWKER PACIFIC INC.

* * *

BEFORE THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

In re Hawker Pacific Inc.,
facility at 11310 Sherman
Way, Sun Valley, California;
San Fernando Valley
Groundwater Investigation
EPA File No. 111.0436

This response is made by Hawker Pacific Inc.

("Hawker Pacific") to the request for information under

CERCLA § 104(e), 42 U.S.C. § 9604(e) ("Third EPA Request"),

made by the United States Environmental Protection Agency

("EPA") by letter dated May 14, 1992, addressed to David

Loklar, regarding Hawker Pacific's facility at 11310 Sherman

Way, Sun Valley, California 91352. Hawker Pacific has

responded to two prior EPA requests for information by

responses dated July 7, 1989 and June 14, 1991.

The person who provided information regarding the facility included in this document is Jeff B. Belzer, who is

currently a Hawker Pacific employee and who can be contacted through Hawker Pacific's undersigned counsel.

This response does not constitute any admission by Hawker Pacific that it has contributed to or is responsible for the San Fernando Valley groundwater contamination referred to in the EPA's request, and Hawker Pacific denies any such contribution or responsibility.

This response includes an exhibit as to which Hawker Pacific claims confidentiality pursuant to CERCLA § 104(e)(7)(E) and (F). The exhibit is enclosed in a separate envelope marked to indicate confidentiality.

Hawker Pacific objects to Instruction 3 of the Request insofar as it seeks to establish a continuing obligation upon Hawker Pacific to report information subsequently discovered or learned by Hawker Pacific, on the grounds that such a continuing request is beyond the scope of EPA authority under CERCLA § 104(e) and would be impracticable or impossible to implement.

Without waiving the foregoing qualifications and objections, Hawker Pacific further responds to the Requests as follows:

1. For all prior operators of the facility, provide copies of all documents relating to the use of trichlorethylene ("TCE") and tetrachlorethylene ("PCE") which were not provided previously to EPA in response to an Information Request.

Hawker Pacific has no such documents other than those documents previously provided to EPA.

Provide a copy of the asset purchase agreement executed 2. by Hawker Pacific, Inc. and Inchcape, PLC on or about April 1, 1987, including any documents pertaining to that agreement.

A copy of the agreement is attached as Exhibit 1. Hawker Pacific claims confidentiality for Exhibit 1 pursuant to CERCLA § 104(e)(7)(E) and (F). The Exhibit is enclosed in a separate envelope marked to indicate confidentiality.

3. Describe the relationship between Hawker Pacific, Inc. and Flight Accessory Services. Provide a copy of the asset purchase agreement executed by Hawker Pacific, Inc. and Flight Accessory Services on or about April 1, 1987. Also, include any documents pertaining to that agreement.

Flight Accessory Services, Inc. was a subsidiary of Inchcape Plc. Hawker Pacific purchased certain assets of Flight Accessory Services, Inc. pursuant to the agreement attached as Exhibit 1.

Provide a copy of the report dated November 26, 1990 prepared by Active Leak Testing, Inc. regarding environmental work completed at the facility.

A copy of a report by that firm dated June 1990, which is referenced in a Law Environmental report previously supplied to EPA and dated November 26, 1990, is attached as Exhibit 2.

Dated: June 24, 1992

Respectfully submitted,

MICHAEL A. MONAHAN GIBSON, DUNN & CRUTCHER

IICHAEL A. MONAHAN

Attorneys for HAWKER PACIFIC

INC.

** ,, % :

MICHAEL A. MONAHAN
GIBSON, DUNN & CRUTCHER
333 South Grand Avenue
Los Angeles, California 90071
(213) 229-7000

Attorneys for HAWKER PACIFIC INC.

BEFORE THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

In re Hawker Pacific Inc.,
facility at 11310 Sherman
Way, Sun Valley, California;
San Fernando Valley
Groundwater Investigation
EPA File No. 111.0436

This response is made by Hawker Pacific Inc.

("Hawker Pacific") to the request for information under

CERCLA § 104(e), 42 U.S.C. § 9604(e) ("Third EPA Request"),

made by the United States Environmental Protection Agency

("EPA") by letter dated May 14, 1992, addressed to David

Loklar, regarding Hawker Pacific's facility at 11310 Sherman

Way, Sun Valley, California 91352. Hawker Pacific has

responded to two prior EPA requests for information by

responses dated July 7, 1989 and June 14, 1991.

The person who provided information regarding the facility included in this document is Jeff B. Belzer, who is

currently a Hawker Pacific employee and who can be contacted through Hawker Pacific's undersigned counsel.

This response does not constitute any admission by Hawker Pacific that it has contributed to or is responsible for the San Fernando Valley groundwater contamination referred to in the EPA's request, and Hawker Pacific denies any such contribution or responsibility.

This response includes an exhibit as to which Hawker Pacific claims confidentiality pursuant to CERCLA § 104(e)(7)(E) and (F). The exhibit is enclosed in a separate envelope marked to indicate confidentiality.

Hawker Pacific objects to Instruction 3 of the Request insofar as it seeks to establish a continuing obligation upon Hawker Pacific to report information subsequently discovered or learned by Hawker Pacific, on the grounds that such a continuing request is beyond the scope of EPA authority under CERCLA § 104(e) and would be impracticable or impossible to implement.

Without waiving the foregoing qualifications and objections, Hawker Pacific further responds to the Requests as follows:

1. For all prior operators of the facility, provide copies of all documents relating to the use of trichlorethylene ("TCE") and tetrachlorethylene ("PCE") which were not provided previously to EPA in response to an Information Request.

Hawker Pacific has no such documents other than those documents previously provided to EPA.

2. Provide a copy of the asset purchase agreement executed by Hawker Pacific, Inc. and Inchcape, PLC on or about April 1, 1987, including any documents pertaining to that agreement.

A copy of the agreement is attached as Exhibit 1. Hawker Pacific claims confidentiality for Exhibit 1 pursuant to CERCLA § 104(e)(7)(E) and (F). The Exhibit is enclosed in a separate envelope marked to indicate confidentiality.

3. Describe the relationship between Hawker Pacific, Inc. and Flight Accessory Services. Provide a copy of the asset purchase agreement executed by Hawker Pacific, Inc. and Flight Accessory Services on or about April 1, 1987. Also, include any documents pertaining to that agreement.

Flight Accessory Services, Inc. was a subsidiary whose ultimate parent entity was of Inchcape Plc. Hawker Pacific purchased certain assets of Flight Accessory Services, Inc. pursuant to the agreement attached as Exhibit 1.

Provide a copy of the report dated November 26, 1990 prepared by Active Leak Testing, Inc. regarding environmental work completed at the facility.

A copy of a report by that firm dated June 1990, which is referenced in a Law Environmental report previously supplied to EPA and dated November 26, 1990, is attached as Exhibit 2.

Dated: June 24, 1992

Respectfully submitted,

MICHAEL A. MONAHAN GIBSON, DUNN & CRUTCHER

MICHAEL A. MONAHAN

Attorneys for HAWKER PACIFIC

INC.

GIBSON, DUNN & CRUTCHER

LAWYERS

333 SOUTH GRAND AVENUE

LOS ANGELES, CALIFORNIA 90071-3197

BOO NEWPORT CENTER DRIVE NEWPORT BEACH, CALIFORNIA 92660-6395 SACRAMENTO

400 CAPITOL MALL SACRAMENTO, CALIFORNIA 95814

CENTURY CITY

2029 CENTURY PARK FAST

LOS ANGELES, CALIFORNIA 90067-3026

ORANGE COUNTY

SAN DIEGO 750 B STREET SAN DIEGO, CALIFORNIA 92101-4605

SAN FRANCISCO ONE MONTGOMERY STREET, TELESIS TOWER SAN FRANCISCO, CALIFORNIA 94104-4505

> SAN JOSE 50 WEST SAN FERNANDO STREET SAN JOSE, CALIFORNIA 95113

DALLAS 1717 MAIN STREET DALLAS, TEXAS 75201-4605

DENVER 1801 CALIFORNIA STREET DENVER, COLORADO 80202-2694

SEATTLE 999 THIRD AVENUE SEATTLE, WASHINGTON 98104-7089

WRITER'S DIRECT DIAL NUMBER 229-7814

(213) 229-7000

TELEX: 674930 GIBTRASK LSA FACSIMILE: (213) 229-7520

June 25, 1991 }

RECEIVED

JULO 2 1992

PHO ENVIRONMENTAL MANAGEMENT, INC

JAS. A. GIBSON, 1852-1922 W. E. DUNN, 1861-1925 ALBERT CRUTCHER, 1860-1931

NEW YORK

200 PARK AVENUE NEW YORK, NEW YORK 10166-0193

WASHINGTON

1050 CONNECTICUT AVENUE N.W. WASHINGTON, D.C. 20036-5306

BRUSSELS

AVENUE LOUISE 222 B-1050 BRUSSELS, BELGIUM

PARIS

104 AVENUE RAYMOND POINCARÉ 75116 PARIS, FRANCE

> LONDON 30/35 PALL MALL LONDON SWIY 5LP

HONG KONG

8 CONNAUGHT PLACE HONG KONG

TOKYO I-I-3 MARUNOUCHI, CHIYODA-KU TOKYO 100, JAPAN

AFFILIATED SAUDI ARABIA OFFICE CHAMBER OF COMMERCE BUILDING P.O. BOX 15870 RIYADH 11454, SAUDI ARABIA

OUR FILE NUMBER

G 37336-00001

VIA FEDERAL EXPRESS

Chris Stubbs South Coast Groundwater Section, H-6-4 United States Environmental Protection Agency Post Office Box 193062 San Francisco, CA 94119-3036

> Hawker Pacific Inc. Re:

11310 Sherman Way

Sun Valley, California; EPA Reference T-4-1

Dear Mr. Stubbs:

Enclosed is a replacement page for page 3 of the RESPONSE OF HAWKER PACIFIC INC. TO THIRD REQUEST FOR INFORMATION PURSUANT TO CERCLA § 104(e) EPA File No. 111.0436, which we mailed to you yesterday. Please substitute this page for the copy that you received, which had dropped several words out of one of the answers.

Very truly yours,

Michael A. Monahan

MAM/par

LL921770.099

060137

) bronahan



HAWKER PACIFIC 11310 SHERMAN WAY SUNLAND, CA 91352

6-14-90

JUNE 1990

SUBMITED BY:

ACTIVE LEAK TESTING, INC. 1300 S. BEACON STREET SUITE 120 SAN PEDRO, CA 90731 (213) 833-8700

TABLE OF CONTENTS

			PAGE
1.0	INTRODUCTION		1
		SITE HISTORY GEOLOGY AND HYDROGEOLOGY	1
2.0	METHODS		2
	2.2	SOIL BORINGS SOIL SAMPLING FIELD SCREENING	2 2 3
3.0	DISCUSSION		3
	3.2 3.3	SOIL BORINGS SOIL DESCRIPTION FIELD SCREENING LABORATORY RESULTS	3 3 3 4
4.0	CONCLUSIONS		4
5.0	RECOMMENDATIONS		4
6.0	LIMITATIONS		5
FIGU	RES		
	SITE LOCATION MAP SCALE PLOT PLAN		
APPE	NDI CE:	S '	
	2. 3	SOIL BORING PROTOCOL UNIFIED SOIL CLASSIFICATION SYSTEM / BORING LOGS SOIL SAMPLING PROTOCOL LABORATORY RESULTS	

1.0 INTRODUCTION

Active Leak Testing, Inc. (ALT) was retained by Hawker Pacific Company to perform a subsurface soil investigation of the property located at 11310 Sherman Way, Sunland, CA (see the Site Location Map in the Figures section). The soil investigation was accomplished by performing soil borings, in key locations, to provide information leading to the determination of the vertical and horizontal extent of the contamination plume.

1.1 SITE HISTORY

Hawker Pacific Company formerly operated one underground storage tank at this facility. The tank has a 280 gallon capacity, and contained waste oil. The tank is located within a concrete containment area with cinderblock walls five feet in height. The containment area also has a 12"x12"x36" sump located in the southeast corner (see plot plan located in the figures section).

1.2 GEOLOGY AND HYDROGEOLOGY

This facility is located in southern Sunland. The site is situated five miles south of Hansen Dam, five miles northeast of the Sepulveda Dam, four miles north of the Los Angeles River, two and one half miles east of the Tujunga Wash, and four miles north of the Santa Monica mountains.

The elevation of this site is 742 feet above sea level. The water table is approximately 270 feet below the surface at this site. The water table in well #4929 was found to be 265.1 feet below grade when last measured on October 28th 1989. This water well is located approximately one third mile northwest of Hawker Pacific. The surface topography slopes at a rate of approximately 50 feet per mile in a southeastern direction. The ground water gradient is ten feet per mile southeastern as well, and the rate of ground water flow is approximately 500 feet per year.

Structurally, the San Fernando Valley is an elongated basin bordered by the Santa Susannah and San Gabriel Mountains in the north, Verdugo Mountains in the east and Santa Monica Mountains in the south. Verdugo Fault is 2.5 miles northeast of the site. This concealed fault continues underground in a northwestern direction to the Los Angeles Reservoir. This is an active fault.

The Los Angeles River and its tributaries drain San Fernando Valley through the Los Angeles Narrows. A major tributary of the Los Angeles River, Tujunga Creek, flows in a southwesternly direction and drains the canyons and valleys in the San Gabriel Mountains. The Verdugo fault is known to be an effective barrier to eastward groundwater flow.

Unconsolidated Pleistocene alluvium and Recent alluvium are the principal water-bearing formations. The Saugus Formation, which underlies the Older alluvium, is made up of continental and marine deposits of conglomerates, sands, silts and clays and in part forms a groundwater reservoir.

The groundwater recharge from percolation is minimal from drainage channels as these are concrete-line. There are a number of major spreading grounds for artificial recharge.

2.0 METHODS

The methods ALT practices for soil borings and soil sampling have been reviewed and approved by a State of California Registered Geologist. These practices are followed to insure the integrity of the information supplied by ALT upon completion of investigation.

2.1 SOIL BORINGS

ALT retains Datum Exploratory, Inc. when soil drilling is required. Datum operates a golf cart mounted drilling rig utilizing continuous flight hollow stem augers. All drilling and sampling equipment is steam cleaned prior to delivery to the site. A full description of the ALT soil boring protocol is provided in Appendix A and the boring locations are provided on the scale plot plan in the Figures section.

ALT maintains boring logs to record descriptions of the lithology penetrated by the boring. All changes in lithology are noted and soil types are described utilizing the Unified Soil Classification System (USCS). The USCS and boring logs are provided in Appendix 2.

2.2 SOIL SAMPLING

The purpose of the soil sampling protocol adopted and followed by ALT is to insure precision and accuracy of the chemical data. Sample integrity is maintained by using steam cleaned augers and core samplers. Core samples are recovered in laboratory washed brass sampling tubes.

During drilling procedures, three core samples are collected at five (5) foot intervals by use of a modified Porter sampler driven by a 140 pound down hole hammer. The uppermost sample provides ALT with a record of soil type and its variations. This sample is also screened for contamination by an Organic Vapor Analyzer (OVA) to provide initial indications of contamination. The bottom two samples are sealed, labeled and placed in an ice chest to maintain the integrity of the sample. A full description of the sample handling procedures are provided in the Soil Sampling protocol in Appendix 3.

Based on the information supplied by field screening of the samples, the Geologist chooses samples that may have indicated signs of contamination during the drilling and sampling process. These samples and the required laboratory analysis are recorded on a Chain-of-Custody document. This document stays with the samples until they are delivered to a State-Certified laboratory for analysis. The samples are usually delivered to the laboratory for analysis within 24 hours.

2.3 FIELD SCREENING

The uppermost sample, recovered from each five foot interval during the soil boring process, is placed in a plastic bag for field screening. The bag sample is screened for organic vapors with a portable Organic Vapor Analyzer (OVA) for indications of possible soil contamination. These readings are taken as the samples are recovered and are recorded on the individual boring logs for reference.

3.0 DISCUSSION

The borings made for this soil investigation were placed in locations which would most likely indicate the presence of any existing contamination. ALT also places boring locations that will provide a representative soil quality and lithology.

3.1 SOIL BORINGS

ALT proposed three soil borings near the facility underground storage tank on the Hawker Pacific property.

Three borings (B1,B2, and B3) in the area of the underground storage tank and sump were completed as proposed. B1 and B2 were advanced to a depth of 20 feet, and B3 was advanced to a depth of 15 feet.

The locations of the three borings in relation to the underground storage tanks and surrounding structures are provided on the site plot plan in the Figures section.

3.2 SOIL DESCRIPTION

The soils encountered were, in general, silty sands and coarse sand and gravel. The soil color was mainly light yellowish brown with some intermittent darker brown layers. The overall moisture content of the soil samples was low but some samples contained moderate moisture levels. Detailed soil descriptions are provided on the individual boring logs in Appendix 2.

3.3 FIELD SCREENING

Samples from the soil borings indicated the presence of contamination in field screening. The highest vapor level encountered was that of OFF THE SCALE for the one foot sample in boring B-3.

3.4 LABORATORY RESULTS

Samples were taken as follows: B1 - 15 feet and 20 feet, B2 - 15 feet and 20 feet and B3 - 1,3,5,10 and 15 feet. All samples were analyzed by EPA Method 418.1 (Total Recoverable Hydrocarbons), and B3- 5 feet was also analyzed by EPA Method 8240 (Volatile Organics).

The 15 and 20 foot samples from B1 indicated 36.3 mg/kg Total Petroleum Hydrocarbons (TPH) each. The detection limit for TPH is 10.0 mg/kg.

The 15 and 20 foot samples from B2 indicated 220 mg/kg and 136 mg/kg TPH respectively. Again well over the detection limit of 10.0 mg/kg.

For boring number three, samples were taken at depths of 1,3,5,10 and 15 feet. Results for TPH are as follows: 1 foot - 38, 637, 3 foot - 22,251, 5 foot - 3,245, 10 foot -17,104, and 15 foot - 354. Again all results are in mg/kg TPH. B3 - five foot was also analyzed Volatile Compounds (GC/MS). Detectable results (over 5.0 ppb) were found for the following constituents: 1,1,1, - Trichloroethylene (6.6 ppb), Trichloroethylene (19.2 ppb), Toluene (550,000 ppb), Trichloroethylene (550,000 ppb) and Xylenes [(total) 584 ppb].

The laboratory documentation of analysis and results, along with the Chain-Of-Custody documentation, is provided in Appendix 4.

4.0 CONCLUSIONS

It is concluded that:

1. The subsurface soils near and around the underground storage tank and sump are contaminated with Petroleum Hydrocarbons in excess of the set action

5.0 RECOMMENDATIONS

It is recommended that:

1. Further subsurface soil investigation be performed in the area of the underground storage tank and sump at this facility to better determine the vertical and horizontal extent of the contamination plume.

6.0 LIMITATIONS

The conclusions and recommendations in this report are based on:

- 1. Information supplied to ALT by the Client.
- 2. The organic vapor measurements acquired on this site.
- 3. The test borings performed at this site.
- 4. Analysis performed by a State-Certified laboratory.
- 5. The observations of field personnel.
- 6. Underground storage tank regulations for the County of Los Angeles.

-

Variations in the soil and groundwater may exist beyond the points examined herein. Changes in groundwater conditions may occur in the future due to variations in rainfall, regional water usage, or other factors not apparent at the time this field investigation was performed.

These services performed by ACTIVE LEAK TESTING, INC. have been conducted in a manner consistent with the level of care and skill ordinarily exercised by members of our profession currently practicing under similar conditions in the Los Angeles County area. No other warrant, expressed or implied, is made.

FIGURES

SITE LOCATION MAP
SCALE PLOT PLAN



* WATER WELL # 4929
elevation - 746.0 feet
depth to ground water - 265.1 feet
date last measured - 10/28/89


ALT


ACTIVE LEAK TESTING INC.

5-20-9 PAGE

CUSTOMER: HAWKER PACIFIC

SITE 11310 SHERMAN WAY





APPENDIX 1

SOIL BORING PROTOCOL

Soil Boring Protocol

Active Leak Testing, Inc. (ALT) practices the following procedures for soil borings. The practice is under supervision of a State of California Registered Geologist. These practices are followed to insure the integrity of the information supplied by ALT upon completion of an investigation.

Preparation

- 1. The Underground Service Alert will be informed of the intention to bore at least 48 hours in advance.
- 2. The Project Manager will establish a safety zone in the area of the drill rig by use of traffic barriers, traffic cones or safety tape. No unauthorized person or persons without proper safety equipment shall enter this zone.
- 3. EM search the area for piping and conduit.
- 4. An appropriate (<1") diameter hole is cored through the existing concrete or asphalt pavement at the desired boring location.
- 5. The subsurface soil is probed, with a metal rod, to a depth of three to four feet.
- 6. Surface pavement is cored to 9" or 12" diameter.

Borings

- 1. The Project Manager supervises the boring procedure to insure that the soil boring is conducted in a proper manner and that no unnecessary risks are taken.
- 2. The Project Manager supervises the personnel to insure that proper safety equipment is worn at all times when within the safety zone.
- 3. Soil borings are performed by truck mounted drilling rigs utilizing continuous flight, 6 to 12 inch hollow stem augers.
- 4. Should a subsurface obstacle be encountered, the boring is halted, the auger is removed and the soil is probed for indications of piping or tanks etc. If the nature of the object is undeterminable the boring will be halted and the hole abandoned.
- 5. The Project Manager or Geologist maintains a boring log to record descriptions of the lithology penetrated by the boring. All changes in lithology are noted and soil types are

described utilizing the Unified Soil Classification System (USCS).

- 6. Soil sampling is conducted following specific protocol for the project.
- 7. When water is unexpectedly encountered the boring shall be discontinued. We do not bore beyond 5' into a tight clay layer under normal circumstances. For water well installations see WW protocol.

Quality Control

- In order to avoid contamination from a previous site, the boring equipment and augers are steam cleaned prior to delivery to the site.
- 2. When multiple borings are required a clean set of augers is used for each boring location. If augers need be reused they are washed with Tri-sodium Phosphate (TSP) soap and rinsed with clean water. Then steam cleaned before use.
- 3. Soil brought to the surface during the boring process is placed in new DOT 55 gallon drums, covered and stored for proper disposal within 60 days.

Completion of boring

No risk to water.

1. For discovery borings which are not to be converted to wells the well is closed by grouting through the hollow stem auger with a mixture of concrete and bentonite (5 to 1). A bottom plug for 1 to 2 feet is followed by sand or soil used to fill boring to about 5 feet below grade. A surface cap is then placed with the grout and a 1 to 2 feet surface cap of concrete finished flush with the surface.

For potential risk to water.

2. The boring is grouted from the bottom with the bentonite concrete mixture; preferably by use of a tremmie so bridging is avoided. A concrete cap/ 2 ft. thick at the surface.

APPENDIX 2

UNIFIED SOIL CLASSIFICATION SISTEM / BORING LOGS

DISCOVERY WE NO. 응 \ CONSTRUCTION	LABORA	ANALYSES FIELD		S. A. S.	SOIL DESC	CRIPTION
TAMPER PROOF WELL COVER PVC CAP CEMENT BETONITE SEAL		-0-				
SLOTTED PVC	Time 10:50	-5- <u>13</u> <u>2-</u> -	SP	_	POWN RXKY 190aded mois	Sand very
	11:07	10 - 27	SP	Poorly Stoles	eowal Rocky graded tea Countz & Gean	
	II: 30	-15- Z\ -25-	sφ	No o	as 5'	
	11:40	20- 17 22	sΡ	SAME	A5 5	
		-25				-
		30-				
		35			•	
		40-				
	LLED TO S	JAMPIE UUD	ER TANK	€ ⊖=	18.	
SURFACE ELEVATION:	DIAMETE	R OF BORING:		et 20'	WATER FOUND AT:	DATE DRILLED: 24APE 40
ALT ACT	IVE LEAK T	ESTING, INC fornia 90731	CUSTOME	B: HAWK	ER PALIFIC TANK	
V S	ian re aro, Cali	tornia 90731	LOGGED BY	r:	DATE: 24APRGO	LOG OF BORING

 ∇

DISCOVERY WE NO. BZ CONSTRUCTION		ANALYSES OF FIELD SO STATE OF		SOIL DE	SCRIPTION
TAMPER PROOF WELL COVER PVC CAP CEMENT BETONITE SEAL SLOTTED PVC PEA GRAVEL	TIME 12:30	-0- -34- -5-	Poor	TBROWN, ROCK My graded, mics	LY SAND. Very acious, mais t
	12:45	9 28	5p. S.	Ame as Abo	UE.
: : : : :	1:00	-15-	SP SA	me As △300	E
	1:15	20-	SP SA	me As ABa)T
		30-			•.
		40			
es: * Deil	LED TO	SAMPLE U	NDER Bldg.	€ = 21°	
FACE ELEVATION:		ESTING, INC	TOTAL DEPTH: 40 ZO CUSTOMER: HA SITE: OLD W	WKER PACIFIC	24APR 90
		EXIDENT BUT	T E CITE . NI N III	1	

H

DISCOVERY WELL NO. 13-3 CONSTRUCTION	LABORATE	NALYSES FIELD		1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	1 3 / 5 / 5 / 5 / 5 / 5 / 5 / 5 / 5 / 5 /	The state of the s	SOIL DES	CRIPTION
TAMPER PROOF WELL COVER PVC CAP CEMENT BETONITE SEAL SLOTTED PVC PEA GRAVEL	TIME 2:00 - 2:05 2:10 2:20	-0- -1 -5- -10- -20- -25-	319 319 310		SP3- SP5'-	- DARK TRAL Musis - LT-A MILL - SAME AND LT BO MILLAL	REFERISH BLACK E ASPHALT AND T AMICALIOUS MEL BROWN SAND ACIOUS ALDIST LIGHT ODOR ZOUND SAND OUS ANDIST SHI	sand with DOTHER STONES Heavy ODOR D Foody graded Moderate ODOR Lace Stones ery Poorly graded
RFACE ELEVATION:		S"	:	TOTA	L 0EP	гн: ^ \ 5°	WATER FOUND AT:	DATE DRILLED: 24APR 10
V ─ Sc	an Pedro, Calif	ornia 9073	1		ED BY		DATE: 24APR 90	LOG OF BORING

Į

ļ

Unified Soil Classification System

Ма	Major Divisons			ols	Soil Description
50	GRAVEL	Clean GEAVEL (Loss Than 1% Finne)	G#	9 0	Well Graded Gravel, Sandy GRAVEL. Must have an equal distribution of Fine and Coarse Gravel. Poorly Graded Gravel, Sandy GRAVEL. Gap Graded, little or to Fines.
COARSE GRAINED	(More Than 50% Material Larger Than *4 Sieves	GRAVEL With Fines	GP GM		Silly Gravel Silly, Sondy GRAVEL.
SOIL (More Than 503)		(More Than 12% Fines)	GC		Clayer GRAVEL Clayer, Sandy GRAVEL.
Material Larger Than The *200	SAND	Clean SANO	sw		Well Graded Send , Gravelly SAND. Must have an equal distribution of fine, medium, and coarse Sand.
Sieve)		(Less Then 49 Steam)	SP		Poorly Graded Sand , Gravelly SAND. Gap Graded, little or se fines.
·		SAND With Fines	SM		Silly SAND, Silly, Growlly SAND.
		(More Than 12% Fines)	sc		Clayey SAND . Clayey, Greenily SAND.
FINE	ene .	·			Inorganic SIN . Sondy or Clayoy SILT . Low to No plasticity
GRAINED		CLAY	CL barranic Cle		Inorganic Clay . Sandy or Silty CLAY. Low to Madium plasticny.
SOIL			OL		Organic SILT or Organic Silty CLAY . Low to Madium plasticity
(Mare Than 50%) Material Small	•				Inorganic SRT , Micoscous or Distancesons Sandy SLT . Elevis SRT . Medium to High plottesty.
ler Than The 200 Sieve)	SILT & CLAY (Liquid Limit More Than 50)		СН		Inorganic CLAY with High planticity.
			ОН		Organic CLAT & SILT with High picaticity.
НІСНІ	Y ORGANIC	SOIL	PT		PEAT & other Highly Organic soils.

Porticle Size Limits

Isieve Operi	<u> </u>	millimeters }	.074	475 7	90 4	17	- 1♥ 0 >=		13 6
SILT	SILT & CLAY			SAND		GRAVEL			
	-		Fine	Median	Coarse	Fine	Coorse	COBBLES	BOULDERS
103 (4-4)	, ,	3.101)	700	*1¢ 6.	e 1	4	<u> </u>		<u>. </u>

Mate. Sociations classifications may be designated by the use of ideal Symbols to the

APPENDIX 3

SOIL SAMPLING PROTOCOL

Soil Sampling Protocol

The purpose of the soil sample protocol adopted and followed by Active Leak Testing, Inc. (ALT) is to insure the precision and accuracy for the laboratory analyzed chemical data. To create a uniform approach for sampling and quality control, the methods are practiced under supervision of a State of California Registered Geologist.

Sampling

- During soil boring procedures three 2 1/2 x 6 inch core samples are recovered at 5 foot intervals by use of a splitbarrel, modified Porter sampler driven by a 140 pound down hole hammer.
- 2. The soil sampling interval may be varied based on the field geologists observations of a major change in lithology or if contamination or water is encountered or if the boring extends beyond 20 feet.
- 3. When contamination is encountered the boring shall continue to a depth of 10 feet below the last indication of contamination.
- 4. When water is unexpectedly encountered the boring shall be discontinued. We do not bore beyond 5' into a tight clay layer under normal circumstamces. For water well installations see WW protocol.
- 5. When a boring is to extend beyond 20 feet the samples will be recovered at 5 foot intervals for the first 20 feet and at 10 foot intervals thereafter.

Field Screening

- The uppermost 6" core sample, recovered at each sampling interval during the sampling process, is placed in a Whirl-Pak plastic bag for field screening.
- 2. The bag sample is screened for organic vapors with a portable Organic Vapor Analyzer (OVA) for indications of possible soil contamination.
- 3. OVA readings are taken for each depth as the core samples are recovered and the values are recorded at the appropriate depth. Core selection for laboratory analysis will be bored in part, on the vapor concentration.

APPENDIX 4 LABORATORY RESULTS

DIVERSIFIED A .ALYTICAL SERVICES

Environmental Laboratory

Inglewood, CA 90303 (213) 671-5346 Fax: (213) 671-7216

LABORATORY REPORT

Reference: Active Leak Testing - Hawker Pacific Soil Samples

Test Methods: EPA Method 8240 for Volatile Compounds (GC/MS)

Date Received: April 25, 1990

Date Analyzed: April 26 - May 7, 1990

Data Reported: May 14, 1990

See attached document for further information. Note:

ANALYTICAL RESULTS All Results in ppb Unless Otherwise Specified

Constituent	B3-5
Chloromethane Vinyl Chloride Bromomethane Chloroethane Acatone 1,1-Dichloroethylene Methylene Chloride 1,2-Dichloroethylene (total) Carbon Disulfide 1,1-Dichloroethane Vinyl Acetate MEK (2-Butanone) Chloroform 1,1,1-Trichloroethane Carbon Tetrachloride 1,2-Dichloroethane Benzene Trichloroethylene 1,2-Dichloropropane Bromodichloromethane MIBK (4-Methyl-2-Pentanone) trans-1,3-Dichloropropene 1,1,2-Trichloroethane Toluene cis-1,3-Dichloropropene 1,1,2-Trichloroethane Tetrachloroethylene Dibromochloromethane Ethybenzene Chlorobenzene Xylenes (total) Styrene Bromoform	00000000000000000000000000000000000000
1,1,2,2-Tetrachloroethane	<5.0

Results continued on next page.

Sample	Depth	Component	Result (mg/kg)	Detection
Number	(feet)	Name		Limit
B-1 B-2 B-2 B-3 B-3 B-3 B-3 B-3	15 20 15 20 1 3 5 10	TPH TPH TPH TPH TPH TPH TPH TPH TPH	36.3 36.3 220 136 38,637 22,251 3,245 17,104 354	10.0 10.0 10.0 10.0 10.0 10.0 10.0

TPH = Total Petroleum Hydrocarbons

< = less than; the number following this sign is the detection limit
for that specific constituent.</pre>

Respectfully Submitted,

Shawn A. Coleman, Laboratory Director/ Analytical Chemist

SPECIAL INSTRUCTIONS HETHOD OF SHIPHEM RELINQUISHED: (PRINT) RELLINQUISHED: (PRINT) William L. LOSER SAMPLED BY: (PRINT) 83 28 S S 33 Sample No. / Identification Address なない PHONE (213) 833-8700 FAX (213) 832-9411 Laboratory: DIVER SIFIED 5 8 ダ 5 ō S w SAN PEDRO, CALIFORNIA 90731 1300 S. BEACON ST. SUITE 120 ACTIVE LEAK TESTING, INC. ZYAPR RELLINQUISHED: (SIGNATURE) TEMPOISHED: (SIGNATURE) SAMPLED BY: (SIGNATURE) 24APR 24APP SHAPE ZYAPR ZHARF ZYAPL 24 APE さる H Date Sampling 1:40 .. 8 2:50 2:10 2:00 2:05 2:20 11:30 Time TIQ. Sample Type RECEIVED BY: (PRINT) LABORATORY (PRINT) RECEIVED BY: (PRINT) AIR PROJECT NAME HANKER PROJECT NUMBER SOLID Containers ス CHAIN OF CUSTODY RECORD \times \times Number #289 NOTES LABORATORY (SIGNATURE) RECEIVED BY: (SIGNATURE) RECEIVED BY: (SIGNATURE) 8010 / 601 PACIFIC 8015 - GAS 8015 - DIESEL 8020 / 602 418.1 TPH × × × DATE PAGE 8240 / 624 × DATE DATE DATE ZYAPR 90 THE THE HHE

I

HETHOD OF SHIPHENT BUE ICE - AUTO SPECIAL DESTRUCTIONS SAMPLED BY: (PRINT) RELINQUISHED: (PRINT) RELINQUISHED: (PRINT) William L. LOSER 82 Sample No. / Identification Address Laboratory: DIVERSIFIED PHONE (213) 833-8700 FAX (213) 832-9411 20 1300 S. BEACON ST. SUITE 120 SAN PEDRO, CALIFORNIA 90731 ACTIVE LEAK TESTING, INC. RELINQUISHED: (SIGNATURE) RELINGUISHED: (SIGNATURE) SAMPLED BY: (SIGNATURE) BYAPR Date Sampling アンス Time <u>L10</u>. Sample Type RECEIVED BY: (PRINT) LABORATORY (PRINT) RECEIVED BY: (PRINT) PROJECT NUMBER # 289 AIR PROJECT NAME HAWKER PACIFIC SOL ID Containers × CHAIN OF CUSTODY RECORD Number NOTES RECEIVED BY: (SIGNATURE) RECEIVED BY: (SIGNATURE) LABORATORY (SIGNATURE) 8010 / 601 8015 - GAS 8015 - DIESEL 8020 / 602 418.1 TPH DATE 24APR 90 PAGE 2 OF 2 8240 / 624 DATE DATE DATE THE THE TIHE

Fax: (213) 671-7216

Unit 3 Inglewood. CA 90303 (213) 671-5346

DIVERSIFIED A VALYTICAL SERVICES Environmental Laboratory

> LABORATORY REPORT

Reference: Active Leak Testing - Hawker Pacific Soil Samples

Test Methods: EPA Method 8240 for Volatile Compounds (GC/MS)

Date Received: April 25, 1990

Data Analyzed: April 26 - May 7, 1990

Date Reported: May 14, 1990

Note: See attached document for further information.

ANALYTICAL RESULTS All Results in ppb Unless Otherwise Specified

Constituent	B3-5
Chloromethane	
Vinyl Chloride	<5.0
Bromomethane	<5.0
Chloroethane	<5.0
Acetone	<5.0
1,1-Dichlorosthylene	<5.0
Methylene Chiorida	<5.0
1,2-Dichloroethylene /total)	<5.0
carbon Distilida	<5.0
1,1-Dichloroethane	<5.0 <5.0
Vinyl Acetata	<5.0
MEK (2-Butanone)	<5.0
Chloroform	<5.0
1,1,1-Trichloroethane	6.6
Carbon Tetrachloride	<5.0
1,2-Dichloroethane	<5.0
Benzene	<5.0
Trichloroethylene	19.2
1,2-Dichloropropane	<5.0
Bromodichloromethane	<5.0
MIBK (4-Methyl-2-Pentanone)	<5.0
trans-1,3-Dichloropropene Toluene	<5.3
cis-1,3-Dichloropropene	550,000
1,1,2-Trichloroethane	<5.0
Tetrachloroethylene	<5.0
Dibromochloromethane	555,000
Ethybenzene	<5.0
Chlorobenzene	<5.0
Xylenes (total)	<5.0
Styrene	584
Bromoform	< 5.0
1,1,2,2-Tetrachloroethane	<5.0
	<5.0

Results continued on next page.

EXHIBITS TO RESPONSE OF HAWKER PACIFIC INC. TO EPA REQUEST FOR INFORMATION PURSUANT TO CERCLA § 104(e) (INCLUDING CONFIDENTIAL INFORMATION)

VOLUME II of II

Exhibits 13-25

INDEX OF EXHIBITS TO RESPONSE OF HAWKER PACIFIC INC. TO EPA REQUEST FOR INFORMATION PURSUANT TO CERCLA § 104(e) (INCLUDING CONFIDENTAL INFORMATION)

Number	<u>Description</u>
1.	Lease from Wagner and Bassinger to Hawker Pacific (Building 1, 2 and 3)
2.	Lease from Industrial Bowling to Hawker Pacific (Building 5).
3.	Lease from Industrial Bowling Corp. to Hawker Pacific
4.	Sealed map of facility.
5.	Law Environmental, Inc. Report (January 4, 1989).
6.	Law Environmental, Inc. Report (August 22, 1989).
7.	Law Environmental, Inc. Report (January 11, 1990).
8.	Law Environmental, Inc. Report (November 26, 1990).
9.	Law Environmental, Inc. Work Proposal (May 22, 1991).
10.	Material Safety Data Sheets
11.	Hazardous Waste Manifests
12.	Sewer Permit
13.	Insurance Policies (1986-1987).
14.	Insurance Policies (1987-1988).
15.	Insurance Policies (1988-1989).
16.	Insurance Policies (1989-1990).
17.	Insurance Policies (1990-1991).
18.	1988 Federal Tax Return.

- 19. 1989 Federal Tax Return.
- 20. 1988 Hawker Siddeley Annual Report.
- 21. 1989 Hawker Siddeley Annual Report.
- 22. 1990 Hawker Siddeley Annual Report.
- 23. 1989 Hawker Pacific Financial Statements.
- 24. Articles of Incorporation.
- 25. By-Laws.

LA911650.030



